

# SHIELD ASSEMBLY (FOLD-UP DESIGN)




## KIT CONTENTS

- 1 FACE SHIELD WITH PROTECTIVE FILM
- 1 ADJUSTMENT TETHER W/ STAY CLIP
- 1 HEADBAND WITH FOLD-ABLE ADJ.



### STEP 1

REMOVE PROTECTIVE FILM FROM MOUNTING HOLES ON BOTH SIDES. IF LEFT ON WHEN ASSEMBLING, SHIELD MAY NOT SNAP IN COMPLETELY. YOU MAY ONLY REMOVE THE FILM FROM OVER THE CONNECTING HOLES RATHER THAN THE WHOLE SHIELD. THE REMAINING FILM YOU CAN REMOVE ONCE ASSEMBLY IS COMPLETE.



### STEP 2

LOCATE HEADBAND AND PRIOR TO SNAPPING SHIELD ON, MAKE SURE TO ORIENT THE HEADBAND PROPERLY. THE FOLD UP STOPPER TAB SHOULD BE FACING DOWN AS SHOWN IN THE PIC. PLEASE MAKE SURE TO FOLLOW THIS ACCORDINGLY TO AVOID HAVING TO REMOVE AND RE-SNAP THE SHIELD. **(\*\*NOTE\*\* SHIELD IS NOT DESIGNED TO BE REMOVED AND RE-APPLIED MULTIPLE TIMES. PLEASE ENSURE PROPER ASSEMBLY FIRST TIME TO AVOID ADDITIONAL FATIGUE TO MOUNTING HOLES)**



### STEP 3

PROCEED TO LOCATE SHIELD WITH PROTECTIVE FILM REMOVED FROM OVER BOTH SIDES OF MOUNTING HOLES AND SNAP INTO PLACE STARTING FROM ONE SIDE AND PROCEEDING ONE BY ONE. EACH MOUNTING HOLE SHOULD MAKE A CLICKING TYPE FEEL. THIS WILL ENSURE IT IS PROPERLY FASTENED INTO PLACE. **(\*\*NOTE\*\* SHIELD IS NOT DESIGNED TO BE REMOVED AND RE-APPLIED MULTIPLE TIMES. PLEASE ENSURE PROPER ASSEMBLY FIRST TIME TO AVOID ADDITIONAL FATIGUE TO MOUNTING HOLES)**



### STEP 4

LOCATE ADJUSTMENT TETHER. LOCATE OVAL OPENING ON REAR OF HEADBAND AND PROCEED TO SLIDE LOOPED SIDE OF TETHER THRU OPENING AS SHOWN IN PIC. FEED LOOPED SIDE TO OPPOSITE END OF HEADBAND AND PLACE AROUND INDENTED SIDE OF HEADBAND AS SHOWN IN PIC.



### STEP 5

ONCE AROUND INDENTED SIDE OF HEADBAND, WHILE HOLDING ONTO INDENTED SIDE OF HEADBAND PULL ON TETHER TOWARDS OPPOSITE END OF HEADBAND. THIS WILL STRETCH THE TETHER ALLOWING IT TO FIT INTO TOP AND BOTTOM INDENTATIONS OF HEADBAND AS SHOWN IN PIC.



### STEP 6

YOUR SHIELD SHOULD BE FULLY ASSEMBLED NOW. YOU CAN ADJUST THE FITMENT ACCORDINGLY BY TAKING ONE HAND AND HOLDING ONTO THE HOLD TAB AND WITH THE OTHER HAND, SQUEEZING THE SPRING LOADED TETHER SLIDER AND SETTING TO YOUR DESIRED LENGTH. THIS WILL EXPAND OR CONTRACT THE HEADBAND ADJUSTMENT